# SILVER SERVICE

### OPENING DOORS FOR BUSINESS

The Dynamic Silver Service team are dedicated to providing responsive, fast and effective service. Our clients depend on us to have their shop fronts and entries opening for business and closing for security.

## DYNAVIEW® by DYNAMIC CLOSURES

SIDE FOLDING POLYCARBONATE AND ALUMINIUM CONCERTINA DOOR



Dynaview® (side folding concertina door) is part of Dynamic Closures' DYNAGLIDE® range. Dynaview has been specially crafted for ease of operation and maximum security, designed to suit a variety of situations including:

- Commercial shop fronts
- Shopping centres
- Shop windows
- Retail outlets
- Serveries
- Counters
- · Bars & restaurants
- Hotel kitchens
- Kiosks
- Cafés

Dynaview is versatile and easy to operate. There are no floor tracks, removable mullions, or the need for complicated bulkheads. The design provides flexibility and can be operated without the need of costly motorisation.

Dynaview offers a quality and economical solution. Purpose built with a robust aluminium and polycarbonate panel curtain construction and equipped with a premium locking and tracking system. Dynaview also accommodates radius openings, allowing it to stack away into a 250mm wide storage pocket.

#### **SPECIFICATIONS**

#### **CURTAIN**

Dynaview polycarbonate panel design shall incorporate 104mm O/A (w) x 101mm (h) truss-like aluminium panels top and bottom of curtain. Curtain shall be 94mm (w) with a clear polycarbonate infill. Maximum height 4600mm.

#### **CURTAIN EDGES**

Shall be **32mm** x **53mm** extruded vertical members (hinges), with top and bottom automatically retractable locking post. One intermediate member shall be provided for every **3000mm** of opening. All intermediate members shall be fitted with adjustable, concealed drop bolts. Intermediate member spacing on counter applications **1800mm** maximum.

#### COLOURS

The standard finish for all visible aluminium components on Dynaview closures is a **clear anodised matt finish**. Optional extra powder coating in Dulux colour range is available.

#### CURTAIN WEIGHT

Curtain weight is **11 kg** per square metre. This may vary depending on locking post types and amounts.

#### LOCKING

Lead posts shall be provided with cylinder locks and guards, operable from both sides. Master keyed cylinders (if required), shall be supplied by others. Top and bottom shoot bolt locking as standard. Dust proof floor sockets shall be provided. Electro-magnetic locking is available as an optional addition.

#### **HEAD TRACK**

The track extruded aluminium **38mm (h)** x **36mm (w).** Curved tracks (where required) are supplied with a standard radius.

#### **STANDARD RADIUS:**

45 degree - 407mm and 559mm 90 degree - 407mm and 559mm

To provide smooth and easy operation for custom curved applications, the radius must be nominated (minimum **1500mm**). For elliptical curves, a template must be provided to Dynamic Silver Service prior to manufacture.



Dynamic Silver Service is continually researching and developing products and reserves the right to change specifications without notice.